

ITEM TECHNICAL CARD

h (mm)	22,0
Material	white zinc plated steel cl.10
Diameter	M20
pitch	1,5
UNI	7473
DIN	982
ISO	7040
m (mm)	16,0
S (mm)	30,0
Rules Description	hex nylon insert lock nuts, high type, fine thread

DESCRIZIONE \ DESCRIPTION:					CATEGORIA \ CATEGORY:		57156ZB.00100		
Self-locking nylon ins. hex nut U7473/D982 fine cl.8 - white zinc plated									
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:				NOTE \ NOTES:			
ESEGUITO DA \ DRAWN BY: RIVIT		DATA:		TRATT. SUPERFICIALE\ SURF. TREATMENT:				Rugosità superficiale generale: General surface roughness:	
CONTROLLATO DA \ CHECKED BY: RIVIT		DATA:		PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:			NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW		
APPROVATO DA \ APPROVED BY: RIVIT		DATA:		DUREZZA \ HARDNESS:	FOGLIO\ SHEET: 1 OF 1	FORMATO FOGLIO: SHEET FORMAT:	A4	METODO 1 (ISO 128) METHOD 1 (ISO 128)	REVISIONE: REVISION:
				PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07			



FASTENERS
& TOOLS



RIVIT.IT