


ITEM TECHNICAL CARD

length (mm)	20
Material	white zinc plated steel 8.8
Diameter	M8
UNI	5932
DIN	912
ISO	4762
D (mm)	13,0
k (mm)	8,0
t (mm)	4,0
b (mm)	28
Rules Description	socket head cap screws, fully threaded, fine threaded
s (mm)	6,0
pitch	1,0

DESCRIZIONE \ DESCRIPTION: <b>Vite TCCE UNI 5932/DIN 912 PF 8.8 ZB M8x1,0x20</b>				CATEGORIA \ CATEGORY: <b>57596ZB.00200</b>	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:	
ESEGUITO DA \ DRAWN BY: <b>RIVIT</b>	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:		
CONTROLLATO DA \ CHECKED BY: <b>RIVIT</b>	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	<b>NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW</b>		
APPROVATO DA \ APPROVED BY: <b>RIVIT</b>	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: <b>1 OF 1</b>	FORMATO FOGLIO: SHEET FORMAT: <b>A4</b>	METODO 1 (ISO 128) METHOD 1 (ISO 128) REVISIONE: REVISION:
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT <b>Mod.P023_07</b>	



**FASTENERS  
& TOOLS**  
RIVIT.IT