

ITEM TECHNICAL CARD



hole diameter (mm)	5,87 ÷ 5,97
d - rivet diameter	6,0
T - head width (mm)	11,5
L - rivet length (mm)	7,9
number of pieces in cartridge (pz)	33
k - head thickness (mm)	1,3
shear strength (N)	1600
tensile strength (N)	3200
grip range (mm)	3,7 ÷ 4,9
body material	aluminium
head type	dome

DESCRIZIONE \ DESCRIPTION: BRAT-Speedriv Alu in cartridge 33pcs DH gr 3,6-4,9 6,0x7,9		CATEGORIA \ CATEGORY: 5868000.17000	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:	NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	METODO 1 (ISO 128) REVISIONE: METHOD 1 (ISO 128) REVISION:
		PESO \ WEIGHT:	Scale \ SCALE: Mod.P023_07



**FASTENERS
& TOOLS**
RIVIT.IT