


ITEM TECHNICAL CARD



T - head width (mm)	18,0
L2 - shank length after fixing (mm)	7,6 ÷ 8,2
L - rivet nuts length (mm)	21,0
k - head thickness (mm)	1,5
grip range (mm)	2,0 ÷ 5,0
d - rivet nut pitch	M6
hole diameter	9,0
body material	steel
head type	large
shank type	open knurled cylindrical

DESCRIZIONE \ DESCRIPTION: FLC-Z-Rivsert Fe TL18 f.9,0 ss2,0-5,0 Zig.ZnNi M6/050		CATEGORIA \ CATEGORY: 5878400.00500	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:	
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	METODO 1 (ISO 128) METHOD 1 (ISO 128)
		PESO \ WEIGHT:	REVISIONE: REVISION:
		FOGLIO \ SHEET: 1 OF 1	CARTIGLIO \ FORMAT Mod.P023_07
		FORMATO FOGLIO: SHEET FORMAT: A4	REVISIONE: REVISION:



**FASTENERS
& TOOLS**
RIVIT.IT