

ITEM TECHNICAL CARD



height (mm)	1630
dimensions (mm)	300x630x1630
model	0752
weight (kg)	62
mandrel capacity (mm)	1 - 16 B16
max drilling capacity steel (mm)	Ø 20
height from ground to work level (mm)	460x275
max drilling capacity on cast iron (mm)	Ø 25
spindle taper (mm)	CM 3
spindle speed (rpm)	(16) 220 ÷ 2840

DESCRIZIONE \ DESCRIPTION: FERVI-Floor drill with drive belt 0752				CATEGORIA \ CATEGORY: 6290500	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:	
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:		
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW		
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: 1 OF 1	FORMATO FOGLIO: SHEET FORMAT: A4	METODO 1 (ISO 128) METHOD 1 (ISO 128) REVISIONE: REVISION:
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07	



**FASTENERS
& TOOLS**
RIVIT.IT