

ITEM TECHNICAL CARD



height (mm)	1630
dimensions (mm)	300x630x1630
model	0752
weight (kg)	62
mandrel capacity (mm)	1 - 16 B16
max drilling capacity steel (mm)	Ø 20
height from ground to work level (mm)	460x275
max drilling capacity on cast iron (mm)	Ø 25
spindle taper (mm)	CM 3
spindle speed (rpm)	(16) 220 ÷ 2840

DESCRIZIONE \ DESCRIPTION: <b>FERVI-Floor drill with drive belt 0752</b>		CATEGORIA \ CATEGORY: <b>6290500</b>	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:	NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: <b>RIVIT</b>	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:
CONTROLLATO DA \ CHECKED BY: <b>RIVIT</b>	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	<b>NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW</b>
APPROVATO DA \ APPROVED BY: <b>RIVIT</b>	DATA:	DUREZZA \ HARDNESS:	METODO 1 (ISO 128) REVISIONE: METHOD 1 (ISO 128) REVISION:
		PESO \ WEIGHT:	CARTIGLIO \ FORMAT <b>Mod.P023_07</b>
			Scale \ SCALE:



**FASTENERS  
& TOOLS**  
RIVIT.IT