




ITEM TECHNICAL CARD

| | |
|-------------------------|-------|
| diamètre d'attaque (mm) | 8,0 |
| d. - diamètre (mm) | 24,0 |
| modèle | FT024 |

| | | | | | | | | |
|----------------------------------------------------------------------------------------------|-------|----------------------------------------------------------------------------------|---------------------------------------------------------------|----------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|-------------------------|
| DESCRIZIONE \ DESCRIPTION: Fraise à défoncer (pour tole, Ac, Alu) ép. Max 5mm d.24 | | | | CATEGORIA \ CATEGORY: | | 0265600 | | |
| MATERIAL \ MATERIAL: | | TRATTAMENTO TERMICO \ HEAT TREATMENT: | | NOTE \ NOTES: | |  FASTENERS & TOOLS  RIVIT.IT | | |
| ESEGUITO DA \ DRAWN BY: RIVIT | DATA: | TRATT. SUPERFICIALE \ SURF. TREATMENT: | Rugosità superficiale generale: General surface roughness: | | | | | |
| CONTROLLATO DA \ CHECKED BY: RIVIT | DATA: | PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]: | | NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW | | | | |
| APPROVATO DA \ APPROVED BY: RIVIT | DATA: | DUREZZA \ HARDNESS: | FOGLIO \ SHEET: 1 OF 1 | FORMATO FOGLIO: SHEET FORMAT: A4 | METODO 1 (ISO 128) METHOD 1 (ISO 128) | | | REVISIONE: REVISION: |
| | | PESO \ WEIGHT: | Scale \ SCALE: | CARTIGLIO \ FORMAT Mod.P023_07 |  | | | |