


ITEM TECHNICAL CARD



| | |
|-----------------------|---|
| longueur (mm) | 16,0 |
| Matière | acier nickelé C15 |
| Diamètre | 4,2 |
| pas | 1,4 |
| UNI | 6955 |
| DIN | 7982C |
| ISO | 7050 |
| Description Normative | vis autotaraudeuses à tête fraisée cruciforme |
| r max (mm) | 1,6 |
| K (mm) | 2,5 |
| d1 (mm) | 8,1 |
| PH | 2 |

| | | | | | |
|--|-------|--|---|---|--|
| DESCRIZIONE \ DESCRIPTION: Phillips cross flat head tapping screw UNI 6955/DIN 7982 nickel | | | | CATEGORIA \ CATEGORY: 03137NK | |
| MATERIALE \ MATERIAL: | | TRATTAMENTO TERMICO \ HEAT TREATMENT: | | NOTE \ NOTES: | |
| ESEGUITO DA \ DRAWN BY: RIVIT | DATA: | TRATT. SUPERFICIALE \ SURF. TREATMENT: | Rugosità superficiale generale: General surface roughness: | | |
| CONTROLLATO DA \ CHECKED BY: RIVIT | DATA: | PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]: | NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW | | |
| APPROVATO DA \ APPROVED BY: RIVIT | DATA: | DUREZZA \ HARDNESS: | FOGLIO \ SHEET: 1 OF 1 | FORMATO FOGLIO: SHEET FORMAT: A4 | METODO 1 (ISO 128) METHOD 1 (ISO 128) REVISIONE: REVISION: |
| | | PESO \ WEIGHT: | Scale \ SCALE: | CARTIGLIO \ FORMAT Mod.P023_07 | |



**FASTENERS
& TOOLS**
RIVIT.IT