



ITEM TECHNICAL CARD

diamètre du trou (mm)	14,0
typologie	ASOC-14
vis (mm)	M5x65,0
diamètre (mm)	15,0
support d'épaisseur maxi (mm)	30,0
espace minimum (mm)	27,0

DESCRIZIONE \ DESCRIPTION: <b>ASOC-14-Ancrage à oeillet fermé M5x65</b>				CATEGORIA \ CATEGORY:		<b>0367200.00250</b>		
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:		  <b>FASTENERS &amp; TOOLS</b>  <b>RIVIT.IT</b>		
ESEGUITO DA \ DRAWN BY: <b>RIVIT</b>	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:					
CONTROLLATO DA \ CHECKED BY: <b>RIVIT</b>	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:		<b>NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW</b>				
APPROVATO DA \ APPROVED BY: <b>RIVIT</b>	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: <b>1 OF 1</b>	FORMATO FOGLIO: SHEET FORMAT: <b>A4</b>	METODO 1 (ISO 128) METHOD 1 (ISO 128)			REVISIONE: REVISION:
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT <b>Mod.P023_07</b>	