


ITEM TECHNICAL CARD

longueur (mm)	16,0
Matière	acier galvanisé noir C15
Diamètre	3,9
pas	1,3
UNI	8119
DIN	7504P
ISO	15482
k (mm)	2,3
Description Normative	vis autoperç. à tête cylind. a/empreinte croisée Ph
d1 (mm)	7,5
PH	2

DESCRIZIONE \ DESCRIPTION: <b>Csk flat head self drilling screw UNI8119/DIN7504P black zinc plated</b>				CATEGORIA \ CATEGORY: <b>04930ZN.01000</b>	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:	
ESEGUITO DA \ DRAWN BY: <b>RIVIT</b>	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:		
CONTROLLATO DA \ CHECKED BY: <b>RIVIT</b>	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	<b>NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW</b>		
APPROVATO DA \ APPROVED BY: <b>RIVIT</b>	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: <b>1 OF 1</b>	FORMATO FOGLIO: SHEET FORMAT: <b>A4</b>	METODO 1 (ISO 128) METHOD 1 (ISO 128) REVISIONE: REVISION:
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT <b>Mod.P023_07</b>	



**FASTENERS  
& TOOLS**  
RIVIT.IT