

ITEM TECHNICAL CARD



longueur (mm)	32,0
Matière	acier galvanisé blanc C15
Diamètre	3,9
pas	1,3
UNI	8119
DIN	7504P
ISO	15482
k (mm)	2,3
Description Normative	vis autoperç. à tête cylind. a/empreinte croisée Ph
d1 (mm)	7,5
PH	2

DESCRIZIONE \ DESCRIPTION: <b>Csk flat head self drilling screw UNI8119/DIN7504P white zinc plated</b>		CATEGORIA \ CATEGORY: <b>04934ZB.00500</b>	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:	NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: <b>RIVIT</b>	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:
CONTROLLATO DA \ CHECKED BY: <b>RIVIT</b>	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	<b>NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW</b>
APPROVATO DA \ APPROVED BY: <b>RIVIT</b>	DATA:	DUREZZA \ HARDNESS:	METODO 1 (ISO 128) METHOD 1 (ISO 128)
		FOGLIO \ SHEET: <b>1 OF 1</b>	REVISIONE: REVISION:
		PESO \ WEIGHT:	Scale \ SCALE:
		CARTIGLIO \ FORMAT <b>Mod.P023_07</b>	



**FASTENERS  
& TOOLS**  
RIVIT.IT