

ITEM TECHNICAL CARD

longueur (mm)	20
Matière	acier cuivré C15
Diamètre	4
DIN	7505A
Description Normative	vis à aggloméré tête fraisée cruciforme
D min/max (mm)	7,64/8,00
K max (mm)	2,35
r1~ (mm)	2
b max (mm)	1,05
N Pozi Recess	2
recess m ~	4,4

DESCRIZIONE \ DESCRIPTION: Flat head chipboard screw DIN 7505A brass plated steel C15 4x20		CATEGORIA \ CATEGORY: 08751OT.00500	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:	
ESEGUITO DA \ DRAWN BY: RIVIT		NOTE \ NOTES:	
DATA:		TRATT. SUPERFICIALE \ SURF. TREATMENT:	
CONTROLLATO DA \ CHECKED BY: RIVIT		Rugosità superficiale generale: General surface roughness:	
DATA:		PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	
APPROVATO DA \ APPROVED BY: RIVIT		NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW	
DATA:		DUREZZA \ HARDNESS:	
PESO \ WEIGHT:		FOGLIO \ SHEET: 1 OF 1	
Scale \ SCALE:		FORMATO FOGLIO: A4	
CARTIGLIO \ FORMAT		METODO 1 (ISO 128) REVISIONE: METHOD 1 (ISO 128) REVISION:	
Mod.P023_07			



**FASTENERS
& TOOLS**
RIVIT.IT