

ITEM TECHNICAL CARD



longueur (mm)	13,
Matière	acier nickelé C15
Diamètre	3,9
pas	1,3
UNI	6955
DIN	7982C
ISO	7050
Description Normative	vis autotaraudeuses à tête fraisée cruciforme
r max (mm)	1,5
K (mm)	2,3
d1 (mm)	7,5
PH	2

DESCRIZIONE \ DESCRIPTION: Phillips cross flat head tapping screw UNI 6955/DIN 7982 nickel				CATEGORIA \ CATEGORY: 09016NK.01000	
MATERIALE \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:	
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:		
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW		
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: 1 OF 1	FORMATO FOGLIO: SHEET FORMAT: A4	METODO 1 (ISO 128) METHOD 1 (ISO 128) REVISIONE: REVISION:
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07	



**FASTENERS
& TOOLS**
RIVIT.IT