




ITEM TECHNICAL CARD

| | |
|------------------------------|-----------|
| diamètre du trou (mm) | 6 |
| longueur de la cheville (mm) | 40 |
| typologie | RRXA06040 |

| | | | | | |
|--|-------|--|--|---|--|
| DESCRIZIONE \ DESCRIPTION: RRX-A-Ancrage rapide a/Boucle CUIVRE+clou CU+Joint 6x40 | | | | CATEGORIA \ CATEGORY: 1040800.00200 | |
| MATERIAL \ MATERIAL: | | TRATTAMENTO TERMICO \ HEAT TREATMENT: | | NOTE \ NOTES: | |
| ESEGUITO DA \ DRAWN BY: RIVIT | DATA: | TRATT. SUPERFICIALE \ SURF. TREATMENT: | Rugosità superficiale generale: General surface roughness: | |  |
| CONTROLLATO DA \ CHECKED BY: RIVIT | DATA: | PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]: | NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW | | |
| APPROVATO DA \ APPROVED BY: RIVIT | DATA: | DUREZZA \ HARDNESS: | FOGLIO \ SHEET: 1 OF 1 | FORMATO FOGLIO: SHEET FORMAT: A4 | METODO 1 (ISO 128) METHOD 1 (ISO 128) |
| | | PESO \ WEIGHT: | Scale \ SCALE: | CARTIGLIO \ FORMAT Mod.P023_07 | REVISIONE: REVISION:  |
|  | | | | | |