

ITEM TECHNICAL CARD



longueur (mm)	32,0
Matière	acier galvanisé noir C15
Diamètre	6,3
pas	1,8
UNI	6955
DIN	7982C
ISO	7050
Description Normative	vis autotaraudeuses à tête fraisée cruciforme
r max (mm)	2,4
K (mm)	3,8
d1 (mm)	12,4
PH	3

DESCRIZIONE \ DESCRIPTION: Phillips cross flat head tapping screw UNI 6955/DIN 7982 black zinc		CATEGORIA \ CATEGORY: 10860ZN	
MATERIALE \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:	NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	METODO 1 (ISO 128) REVISIONE: METHOD 1 (ISO 128) REVISION:
		PESO \ WEIGHT:	Scale \ SCALE: Mod.P023_07
		FOGLIO \ SHEET: 1 OF 1	FORMATO FOGLIO \ SHEET FORMAT: A4



**FASTENERS
& TOOLS**
RIVIT.IT