


ITEM TECHNICAL CARD

| | |
|-----------------------|---|
| longueur (mm) | 16,0 |
| Matière | acier galvanisé blanc C15 |
| Diamètre | 4,8 |
| pas | 1,6 |
| UNI | 6955 |
| DIN | 7982C |
| ISO | 7050 |
| Description Normative | vis autotaraudeuses à tête fraisée cruciforme |
| r max (mm) | 1,9 |
| K (mm) | 3,0 |
| d1 (mm) | 9,5 |
| PH | 2 |

| | | | |
|--|-------|--|---|
| DESCRIZIONE \ DESCRIPTION: Phillips cross flat head tapping screw UNI 6955/DIN 7982 white zinc | | CATEGORIA \ CATEGORY: 18045ZB.01000 | |
| MATERIAL \ MATERIAL: | | TRATTAMENTO TERMICO \ HEAT TREATMENT: | NOTE \ NOTES: |
| ESEGUITO DA \ DRAWN BY: RIVIT | DATA: | TRATT. SUPERFICIALE \ SURF. TREATMENT: | Rugosità superficiale generale: General surface roughness: |
| CONTROLLATO DA \ CHECKED BY: RIVIT | DATA: | PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]: | NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW |
| APPROVATO DA \ APPROVED BY: RIVIT | DATA: | DUREZZA \ HARDNESS: | METODO 1 (ISO 128) METHOD 1 (ISO 128) |
| | | FOGLIO \ SHEET: 1 OF 1 | REVISIONE: REVISION: |
| | | PESO \ WEIGHT: | CARTIGLIO \ FORMAT Mod.P023_07 |
| | | Scale \ SCALE: |  |



**FASTENERS
& TOOLS**
RIVIT.IT