


ITEM TECHNICAL CARD



Matière	acier brut C60
Diamètre	48,0
UNI	8842A
DIN	6798A
S (mm)	1,6
pour vis	M30
diamètre intérieur (mm)	31,0

DESCRIZIONE \ DESCRIPTION:		CATEGORIA \ CATEGORY:		20910GR	
Serrated external lock washer UNI 8842A/DIN 6798A plain steel					
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:	
ESEGUITO DA \ DRAWN BY:	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale:		
RIVIT			General surface roughness:		
CONTROLLATO DA \ CHECKED BY:	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]:	NON SCALARE IL DISEGNO		
RIVIT		HEAT TREATMENT (SURF) DEPTH [mm]:			
APPROVATO DA \ APPROVED BY:	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET:	FORMATO FOGLIO:	METODO 1 (ISO 128)
RIVIT			1 OF 1	A4	METHOD 1 (ISO 128)
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT	REVISIONE: REVISION:
				Mod.P023_07	



FASTENERS & TOOLS
 RIVIT.IT