


ITEM TECHNICAL CARD

couple (Nm)	861
modèle	942 PC3 1/2
impulsions par minute	1650
pression de travail d'air (bar)	6,2
vibrations (m/s ²)	9,57
attaque	1/2"
vitesse sans charge (g/min)	10000
entrée d'air	1/4"
consommation d'air (l/min)	127

DESCRIZIONE \ DESCRIPTION: USAG-Compact Impact Wrench 942 PC3 1/2				CATEGORIA \ CATEGORY: 5634300	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:	
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:		
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW		
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: 1 OF 1	FORMATO FOGLIO: SHEET FORMAT: A4	METODO 1 (ISO 128) METHOD 1 (ISO 128)
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07	REVISIONE: REVISION: 



**FASTENERS
& TOOLS**
RIVIT.IT