




ITEM TECHNICAL CARD

diamètre de la tige (mm)	6
dimensions (mm)	50x30
modèle	RGM050/30F
Matière	toile/tissu abrasif
chiffon	A/O-F
utilisation	acier, aluminium, bois, fonte

DESCRIZIONE \ DESCRIPTION: <b>FERVI-Mixed nonwoven and cloth wheels with shaft Alox 50x30F</b>		CATEGORIA \ CATEGORY:		<b>6276600</b>	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:	
ESEGUITO DA \ DRAWN BY: <b>RIVIT</b>	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:		
CONTROLLATO DA \ CHECKED BY: <b>RIVIT</b>	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	<b>NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW</b>		
APPROVATO DA \ APPROVED BY: <b>RIVIT</b>	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: <b>1 OF 1</b>	FORMATO FOGLIO: SHEET FORMAT: <b>A4</b>	METODO 1 (ISO 128) METHOD 1 (ISO 128)
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT <b>Mod.P023_07</b>	REVISIONE: REVISION: 
				 <b>FASTENERS &amp; TOOLS</b> RIVIT.IT	