




ITEM TECHNICAL CARD

diamètre de la tige (mm)	6
dimensions (mm)	50x30
modèle	RGM050/30VF
Matière	toile/tissu abrasif
chiffon	A/O-VF
utilisation	acier, aluminium, bois, fonte

DESCRIZIONE \ DESCRIPTION: FERVI-Mixed nonwoven and cloth wheels with shaft Alox 50x30VF		CATEGORIA \ CATEGORY:		6276700	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:	
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:		
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW		
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: 1 OF 1	FORMATO FOGLIO: SHEET FORMAT: A4	METODO 1 (ISO 128) METHOD 1 (ISO 128)
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07	REVISIONE: REVISION: 
				 FASTENERS & TOOLS RIVIT.IT	