


ITEM TECHNICAL CARD

| | |
|--------------------------|-------------------------------|
| diamètre de la tige (mm) | 6 |
| dimensions (mm) | 60x30 |
| modèle | RGM060/30M |
| Matière | toile/tissu abrasif |
| chiffon | A/O-M |
| utilisation | acier, aluminium, bois, fonte |

| | | | | | |
|---|-------|--|---|---|--|
| DESCRIZIONE \ DESCRIPTION: FERVI-Mixed nonwoven and cloth wheels with shaft Alox 60x30M | | | | CATEGORIA \ CATEGORY: 6276800 | |
| MATERIAL \ MATERIAL: | | TRATTAMENTO TERMICO \ HEAT TREATMENT: | | NOTE \ NOTES: | |
| ESEGUITO DA \ DRAWN BY: RIVIT | DATA: | TRATT. SUPERFICIALE \ SURF. TREATMENT: | Rugosità superficiale generale: General surface roughness: | | |
| CONTROLLATO DA \ CHECKED BY: RIVIT | DATA: | PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]: | NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW | | |
| APPROVATO DA \ APPROVED BY: RIVIT | DATA: | DUREZZA \ HARDNESS: | FOGLIO \ SHEET: 1 OF 1 | FORMATO FOGLIO: SHEET FORMAT: A4 | METODO 1 (ISO 128) METHOD 1 (ISO 128) |
| | | PESO \ WEIGHT: | Scale \ SCALE: | CARTIGLIO \ FORMAT Mod.P023_07 | REVISIONE: REVISION:  |



**FASTENERS
& TOOLS**
RIVIT.IT