


ITEM TECHNICAL CARD

Lunghezza (mm)	16
Materiale	acciaio ottonato C15
Diametro	2,5
DIN	7505A
Descr. Normativa	viti truciolari testa svasata croce
D min/max (mm)	4,7/5,0
K max (mm)	1,4
r1~ (mm)	1,5
b max (mm)	0,7
N Pozi Recess	1
recess m ~	3

DESCRIZIONE \ DESCRIPTION: Truciolare TSP+ DIN 7505A C15 OT 2,5x16				CATEGORIA \ CATEGORY: 10282OT.00500	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:	
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:		
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW		
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: 1 OF 1	FORMATO FOGLIO: SHEET FORMAT: A4	METODO 1 (ISO 128) METHOD 1 (ISO 128) REVISIONE: REVISION:
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07	



**FASTENERS
& TOOLS**
RIVIT.IT