



ITEM TECHNICAL CARD

Lunghezza (mm)	40
Materiale	acciaio ottonato C15
Diametro	4
DIN	7505A
Descr. Normativa	viti truciolari testa svasata croce
D min/max (mm)	7,64/8,00
K max (mm)	2,35
r1~ (mm)	2
b max (mm)	1,05
N Pozi Recess	2
recess m ~	4,4

DESCRIZIONE \ DESCRIPTION: Truciolare TSP+ DIN 7505A C15 OT 4x40				CATEGORIA \ CATEGORY:		33521OT.00500	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:			
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:				
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:		NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW			
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: 1 OF 1	FORMATO FOGLIO: SHEET FORMAT: A4	METODO 1 (ISO 128) METHOD 1 (ISO 128)	REVISIONE: REVISION:	FASTENERS & TOOLS  RIVIT.IT
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07	