

ITEM TECHNICAL CARD



Lunghezza (mm)	20
Materiale	acciaio C15
Diametro	5
DIN	7505B
Descr. Normativa	viti truciolari testa cilindrica croce
D min/max (mm)	9,44/9,80
K min/max (mm)	3,20/3,50
r1~ (mm)	9,98
b max (mm)	1,45
N Pozi Recess	2
recess m ~	5

DESCRIZIONE \ DESCRIPTION: Truciolare TC+ DIN 7505B C15 GR 5x20		CATEGORIA \ CATEGORY: 52167GR.00500	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:	NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	METODO 1 (ISO 128) METHOD 1 (ISO 128)
		PESO \ WEIGHT:	REVISIONE: REVISION:
		FOGLIO \ SHEET: 1 OF 1	CARTIGLIO \ FORMAT Mod.P023_07
		FORMATO FOGLIO: SHEET FORMAT: A4	



**FASTENERS
& TOOLS**
RIVIT.IT